

The Ultimate High Performance Cutting Lubricant

JET9 LX

Stoughcool's Jet9 LX is a moderate-to-heavy-duty hybrid micro-emulsion. Stoughcool Jet9 LX has a very tight emulsion for excellent tramp oil rejection keeping sumps and machines clean! Formulated for ferrous and non-ferrous materials and coupled with an EP lubricant, it's recommended to cut a wide range of materials. Stoughcool Jet9 LX utilizes our C80 Shield™ Technology making it bio-resistant against bacteria and mold and provides excellent sump life measured in years! Absolutely no sump stench, no bad odors!

Jet9 LX offers these advantages for:

- Extended sump life measured in years
- Excellent lubricity, excellent tool life
- Great for high pressure systems, low foaming
- No formaldehyde release biocides
- Uses C80 Shield™ Technology Eliminating sump stench
- Extremely stable even in hard water conditions
- For cutting ferrous and non-ferrous materials

STOUGHCOOL
WE KNOW COOLANT.

Appearance	Yellow to Light Amber
PH@ 5%	9.3
Density lbs./gal.	8.47
Grinding Dilution Recommendation	3%-to-6%
Machining Dilution Recommendation	5%-to-10%
Refractometer Multiplier	1.5



www.stoughcool.com

Stoughcool Jet9 LX does not contain nitrites, sulfur, formaldehyde-release biocides, phenolic biocides, triazine or DCHA. Not for use on Magnesium.